


Once Fabrics are stacked on top of each other, cut through all layers of fabrics, so that the grey areas from the outside of the template are cut away. You may prefer to paste your template onto cardboard, then trim away the grey areas from the template and then trace the finished template onto the stacked fabrics.

Pin layers together then cut with scissors.




Sew a ¼" line from the outside of all edges through all layers. Trim the excess fabrics from the four outer pointed corners. ( curved arrows)

Turn right sides out and press well.

Fold and press ¼" on the first foldline for the outer pieces, at the straight side edges.

• If you are putting in a wire nose piece, cut a 3 ½" piece of covered wire and push against the seam centering at the top edge.



Topstitch the outer edge 1/8" or less from the edge, at the sides top stitch the first folded edge.

Box the Outer edges of the wire as shown.

Fold Sides in 5/8" on the second foldine and secure with pins. Stitch this folded edge down.

Fold top and bottom edges towards the centre, on the foldlines. Press well.

Mark the last topstitching lines 1 ¼" in from both sides.

Topstitch on the fold lines and along the 1 ¼" marked lines through all layers.

Thread a shoe lace or t-shirt tie through side openings with the loop at the bottom.

Thread both ends of the ties towards which are to the top of head through a bead which acts as a stopper for adjusting.